



**Declaration of performance
No. BCN I05 J0V**

1. Unique identification code of the product-type : **BCN I05 J0V**
2. **SE 6**
H – factory 378 09 Nová Ves nad Lužnicí
3. **Liquid-applied water impermeable product for use beneath ceramic tiling bonded with adhesives (type / class C2 according to EN 12004) in the internal environment.**
4. **LB Cemix, s.r.o., Tovární ulice č.p. 36, 373 12 Borovany, Czech Republic**
5. ---
6. System of assessment and verification of constancy of performance of the construction product : **3**
7. **NO 1020 – Technical and Test Institute for Construction Prague, s.p., Prosecká 811/76a, 190 00 Praha 9, Czech Republic**
- issued a Report on the determinatin of the product
No. 1020 – CPR – 020030353
8. ---
- 9.

Essential characteristics	Performance	Harmonised technical specification
High initial tensile adhesion strength	≥ 0,5 N/mm ²	EN 14891:2012
High tensile adhesion strength after water immersion	≥ 0,5 N/mm ²	EN 14891:2012
High tensile adhesion strength after heat ageing	≥ 0,5 N/mm ²	EN 14891:2012
High tensile adhesion strength after calcium water immersion	≥ 0,5 N/mm ²	EN 14891:2012
High tensile adhesion strength after freeze-thaw cycles	NPD	EN 14891:2012
Waterproof	no penetration	EN 14891:2012
Crack bridging ability	≥ 0,75 mm	EN 14891:2012

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by : **Petr Semera, Production and Technical Director, LB Cemix, s.r.o., Borovany**