


TECHNICKÝ LIST /

CL 805

Cleaning agents



APPLICATION:

This is a special product intended for removal of residues of epoxy adhesive and, in particular, jointing materials. Residues are only to be removed manually. The product must be applied undiluted.

COMPOSITION:

Colourless liquid containing solvents and organic solvents (acetone).

TECHNICAL PARAMETERS:

Ph value	8
Flash point	below 23°C
Approximate coverage:	1 litre of this product for approx. 1 to 2 m ² of moderately polluted area

PROCESSING:

The surface to be cleaned must first be washed in the usual way. Removal of dried residues should first be tried on a small, less visible area of surface, on which the residues will be removed. Perform the test removal and subsequent standard removal of all residues manually, using a cloth, or brush moistened in the cleaning agent. Apply the uniform layer of the product on the surface being cleaned, leave it there for about 1-10 minutes, then remove the product and epoxy residues with a cloth, or a plastic spatula. If epoxy residues form a thick layer, you can repeat the entire cycle until all epoxy residues are removed.

Caution: The cleaning agent should never be applied directly to the surface as it may result in excessive removal of protective films and waxes, or, in the worst case (in improper product handling), damage to the surface. Wear suitable protective equipment while handling the product.

CAUTION:

- Before using this product, please read the instructions for use carefully, and follow the manufacturer's instructions.
- Work only in well-ventilated areas. When working, do not smoke, drink, or work near children.
- The product is a slightly flammable liquid (flash point below 23°C).
- This product may etch the surface of grouting materials, or other materials than ceramics.
- Unused residues and contaminated containers should be disposed as of hazardous wastes (see the Safety Data Sheet).

FIRST AID:

In the event of health problems, or if in doubt, contact your doctor. Prior to starting first aid, avoid further exposure to the product. Vapours may cause drowsiness and dizziness. If inhaled, remove the victim to a well-ventilated area, loosen clothing, and seek medical advice. In contact with skin, repeated exposure may cause skin dryness or cracking. If irritation occurs, rinse the affected area thoroughly with water jet for at least 10 minutes. Get medical attention if any discomfort continues. Irritating to eyes. If improperly handled, the product may come into contact with the eyes. Affect contact with the eyes differ contact with the eye medical advice.

TEL	+420 378 021 111	BANK DETAILS: Česká spořitelna, a. s.
FAX	+420 378 021 119	6221912/0800
E-MAIL	info@rako.cz	Company ID number 25238078
WEB	www.rako.cz	Tax ID number CZ25238078
	FAX E-MAIL	FAX +420 378 021 119 E-MAIL info@rako.cz

SYSTEM

TECHNICKÝ LIST /

SAFETY AND HYGIENE REGULATIONS: Warning symbol:

Xi irritant, F Highly flammable

- R 11 R 36 Highly flammable.
- Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Keep out of the reach of children. R 66
- R 67 S 2
- S 7/9 Keep container tightly closed and in a well-ventilated place.
- S 16 Keep away from sources of ignition - no smoking.
- Avoid contact with skin and eyes. S 24/25
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If swallowed, seek medical advice immediately and show this container or label. S 26
- S 46

STORAGE:

- If the product is stored in dry, covered and clean warehouses, protected against atmospheric influences, at temperatures from + 10°C to + 25°C, the shelf life is
- 36 months. The expiration date is specified on the packaging.
- Maximum permissible quantity of the product for the recommended storage conditions: 20000 I.

SHIPPING:

1000 ml PE bottle with a protective cap.

QUALITY:

- The product quality is regularly checked in the manufacturer's laboratories. ٠
- The distributor applies a certified quality management system, according to ISO 9001.

DISTRIBUTOR:

LASSELSBERGER, s.r.o., Adelova 2549/1, 320 00 Pilsen - Jižní Předměstí

VALIDITY:

Since 1 August 2013

We reserve the right to make any changes that are the result of technical progress. This issue cancels and supersedes all previous issues.

LASSELSBERGER, s.r.o. Adelova 2549/1	TEL FAX	+420 378 021 111 +420 378 021 119
320 00 Plzeň - Jižní Předměstí	E-MAIL	info@rako.cz
Czech Republic	WEB	www.rako.cz

BANK DETAILS: Česká spořitelna, a. s. 6221912/0800 Company ID number 25238078 Tax ID number CZ25238078