

### TECHNICKÝ LIST /

# **CL 810**

### Cleaning agents



Cleaning agent for daily cleaning for grease and oil removal

### APPLICATION:

A concentrated, non-foaming agent intended for the dilution and industrial cleaning of all hard water and alkali resistant floor surfaces. This product is suitable mainly for PVC and linoleum surfaces (including waxed surfaces), glazed and unglazed tiles, granite, marble and limestone surfaces, terraces, brick and concrete surfaces (including poured floors), rubber floors, floors in sports hall, varnished parquet floors and floor boards.

The product is characterised with the extreme tolerance to surfaces, and is 100% biodegradable.

It should not be used on untreated, unvarnished wooden floors.

**COMPOSITION:** lonogenic and nonionic surfactants, isopropyl alcohol, butoxyethanol, sodium hydroxide, high-molecular-weight alcohols, alkylamine sodium carboxylate, pentasodium triphosphate, and perfumes.

Amount of water	Dosage of CL 810 according to the degree of contamination*) [ml]		
	1	2	3
1 litre			
10 litres	40	70	100
pH of solution	8.5	8.7	8.8
Approximate coverage:	1 litre of this product is intended for 1000 to 400 m² of surfaces to be cleaned		

<sup>\*)</sup> If the table fields remain empty, the product is used undiluted.

### PROCESSING:

Floor surfaces are cleaned manually, using a mop, a floor washing machine, or a floor disk machine, with a brush, or a pad (selection is made according to a surface type). Continuous surface washing with clean water is recommended.

While handling the product, the use of protective working equipment is recommended.

### CAUTION:

- Before using this product, please read the instructions for use carefully, and follow the manufacturer's instructions.
- Avoid contact with skin and eyes, and work in a well ventilated area
- It is appropriate to use safety goggles or face shield, and protective gloves.
- When working, do not smoke, drink, or work near children.
- After dilution of the product to less than 30% solution, the product does not fall under the classification of hazardous chemical substances.
- Unused residues and contaminated containers should be disposed as of hazardous wastes (see the Safety Data Sheet).
- Only completely emptied and clean packaging may be handed over to recycling.

### FIRST AID:

Prior to starting first aid, avoid further exposure to the product. If inhaled (considered only at high concentrations and after prolonged exposure in non-ventilated areas), remove the victim to a well-ventilated area, loosen clothing, and, according to the victim's condition, seek medical advice. After contact with skin, rinse the affected area thoroughly with water jet for at least 15 minutes. Get medical attention if any discomfort continues. May cause sensitisation by skin contact through repeated exposure. In the event of suspicion of sensitisation, seek medical advice immediately. After contact with the eye mucous membrane, rinse the conjunctival sac with water for 10 minutes, and seek medical advice. If swallowed, rinse mouth with water. Do not induce vomiting! Seek prompt medical advice. If the symptoms of any affection (irritation) caused by contact with the product do not subside after providing first aid, seek medical advice.

LASSELSBERGER, s.r.o. TEL +420 378 021 111 BANK DETAILS: Česká spořitelna, a. s.

Adelova 2549/1 FAX +420 378 021 119 6221912/0800

320 00 Plzeň - Jižní Předměstí E-MAIL info@rako.cz Company ID number 25238078 Czech Republic WEB www.rako.cz Tax ID number CZ25238078



## TECHNICKÝ LIST /

### SAFETY AND HYGIENE REGULATIONS:

Warning symbol: Xi irritant
R 36/38 Irritating to eyes and skin.
S 2 Keep out of the reach of children.

S 24/25 Avoid contact with skin and eyes.
S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S 46 If swallowed, seek medical advice immediately and show this container or label.

### STORAGE:

- If the product is stored in dry, covered and clean warehouses, protected against atmospheric influences, at temperatures from + 10°C to + 25°C, the shelf life is 36 months. The expiration date is specified on the packaging.
- Maximum permissible quantity of the product for the recommended storage conditions: 20,000 I.

### SHIPPING:

1000 ml PE bottle with a protective cap.

#### QUALITY:

- The product quality is regularly checked in the manufacturer's laboratories.
- The distributor applies the certified quality management system, according to ISO 9001.

### DISTRIBUTOR:

LASSELSBERGER, s.r.o., Adelova 2549/1, 320 00 Plzeň – Jižní Předměstí

### VALIDITY:

Since 1 August 2013

We reserve the right to make any changes that are the result of technical progress. This issue cancels and supersedes all previous issues.