

DSAT

Accessories



PE dilatation and separation self-adhesive tape

APPLICATION:

A single-sided adhesive foam tape, suitable for the creation of mechanical and sound dilation along the circumference of floor structures – good adhesion to many bases, such as plastic materials, including polycarbonate, wood, metal, and glass.

For the separation of applied layers of materials in LBCS system solutions.

It reliably interrupts the sound bridge, and avoids undesirable contacts of structures.

The tape is silicone-free, therefore, it can be used in facilities that require its application, such as paint shops, etc.

This product is ideal for contact with silicone sealants if adhesion of sealant is not required, for example, to define the bottom of a joint.

Advantages:

- rapid, easy and smart application;
- good resistance to ageing.

COMPOSITION:

Separation foam material, free of softeners on the basis of PE, with a closed cell structure, provided with a rubber adhesive on one side and a PP layer on the other side.

TECHNICAL PARAMETERS:

Tensile strength:	in the longitudinal direction	0.28 MPa
	in the transverse direction	0.18 MPa
Elongation at break:	in the longitudinal direction	125%
	in the transverse direction	105%
Volume weight		approx. 25 kg/m ³
Thickness		3 mm
Thermal resistance		-30°C to +85°C
Application temperature		+5°C to +35°C

BASE PREPARATION:

The bases must be dry, degreased, free of dust, dirt, and loose particles. Absorbent bases should be penetrated using PE 202.

PROCESSING:

Uncoil the tape from a roll, measure, and cut-to-length as needed. Then, apply the product directly on the prepared base surface. Press the tape firmly to the base. If the material with a cover foil is used, the protective strip must be removed before application.

LASSELSBERGER, s.r.o.
Adelova 2549/1
320 00 Plzeň - Jižní Předměstí
Czech Republic

TEL +420 378 021 111
FAX +420 378 021 119
E-MAIL info@rako.cz
WEB www.rako.cz

BANK DETAILS: Česká spořitelna, a. s.
6221912/0800
Company ID number 25238078
Tax ID number CZ25238078

TECHNICKÝ LIST /

CAUTION:

- Reduced resistance to UV radiation (must be covered)!
- Unused residues should be disposed as of other hazardous wastes (see the Safety Data Sheet).
- Only completely clean material residues and paper packaging (including central parts of paper) may be handed over to recycling.

SAFETY AND HYGIENE REGULATIONS:

This product is not classified as a dangerous substance.

STORAGE:

If the product is stored in the original packaging in a dry place at temperatures from + 5°C to + 25°C, the shelf life 24 months. The expiration date is specified on the packaging.

SHIPPING:

Rolls with a length of 30 m, and with widths of 25 and 65 mm.

QUALITY:

- The product quality is regularly checked in the manufacturer's laboratories.
- The distributor applies a certified quality management system, according to ISO 9001.

DISTRIBUTOR:

LASSELSBERGER, s.r.o., Adelova 2549/1, 320 00 Pilsen – Jižní Předměstí

VALIDITY:

Since 1 August 2013

We reserve the right to make any changes that are the result of technical progress. This issue cancels and supersedes all previous issues.

LASSELSBERGER, s.r.o.
Adelova 2549/1
320 00 Plzeň - Jižní Předměstí
Czech Republic

TEL +420 378 021 111
FAX +420 378 021 119
E-MAIL info@rako.cz
WEB www.rako.cz

BANK DETAILS: Česká spořitelna, a. s.
6221912/0800
Company ID number 25238078
Tax ID number CZ25238078

The company is registered in the Companies Register, administered by the Regional Court in Plzeň, Section C, File 22719