

TECHNICKÝ LIST /

CL 807

Smoothing agent



Smoothing agent for flexible sealants

APPLICATION:

The smoothing agent is a ready-to-use product intended for sealed joints from polyurethane and silicone sealants. The smoothing agent is a new alternative for smoothing over joints, allowing subsequent repair of sealant after application.

COMPOSITION:

Preservatives (Benzyl alcohol, Bronopol, 3-Iodoprop-2-yn-1-yl-N-butylcarbamate).

PROCESSING

The product can be sprayed directly over the surface of the applied sealant.

- Safe for silicones and sealants
- Ready-to-use
- Excellent agent for smoothing

Physical and chemical properties, and design	
Physical form	Liquid
Chemical base	Anionic surfactants
Density	1 g/cm³
Colour	Transparent
Ph value	6.5 - 8.0
Silicone free	Yes
Min./max. processing temperature	0 to 40°C
Boiling point	100°C
Volume	750, 5000 ml
Design	PVC packaging

CAUTION:

- Before using this product, please read the instructions for use carefully, and follow the manufacturer's instructions.
- Avoid contact with eyes
- Only completely emptied and clean packaging may be handed over to recycling.

FIRST AID

After eye contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Dispose of contents/container according to local regulations.

LASSELSBERGER, s.r.o. TEL +420 378 021 111 BANK DETAILS: Česká spořitelna, a. s. Adelova 2549/1 FAX +420 378 021 119 6221912/0800

320 00 Plzeň - Jižní Předměstí E-MAIL info@rako.cz Company ID number 25238078 Czech Republic WEB www.rako.cz Tax ID number CZ25238078



TECHNICKÝ LIST /

SAFETY AND HYGIENE REGULATIONS: Warning symbol:

- R 36 Irritating to eyes.
- S 2 Keep out of the reach of children.
- S 25 Avoid contact with eyes.
- S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- S 46 If swallowed, seek medical advice immediately and show this container or label.

STORAGE:

- Protect against frost.
- If the product is stored under these conditions at temperatures from + 5°C to + 30°C, the shelf life is 36 months from the date of manufacture.
 The expiration date is specified on the packaging.

SHIPPING:

750 ml — 18 pieces in a cardboard box, 816 pieces on a pallet

5 I - 128 pieces on a pallet

QUALITY:

- The product quality is regularly checked in the manufacturer's laboratories.
- The distributor applies a certified quality management system, according to ISO 9001.

DISTRIBUTOR

LASSELSBERGER, s.r.o., Adelova 2549/1, 320 00 Plzeň — Jižní Předměstí

VALIDITY:

Since 1 May 2018

We reserve the right to make any changes that are the result of technical progress. This issue cancels and supersedes all previous issues.

Tax ID number CZ25238078