

Technical data sheet

Product: **WLRMG722**

Color: **white-grey**

Nominal size: **40x2 cm**

Declared size: **398x20x12,5 mm**

Surface: **flat matt**

Serie: **Extra**

Norm: **STO 030-060753**

Declaration: **P 04**

Group of goods: **wall tile - listel**

Product type: **relief listel**

Technical characteristics

Tolerance - Length/width

Tolerance - Thickness

Surface quality

Water absorption

Coefficient of linear thermal expansion

Thermal shock resistance

Crazing resistance

Freeze-thaw resistance

Durability for: internal use

Bond strength/adhesion-cem. adhesives

Bond strength/adhesion-dispers. adhesiv.

Bond strength/adhesion-rea. resin adhes.

Bond strength/adhesion-mortar

Moisture expansion

Reaction to fire

Resistance to low conc.of acids/alkalis

Resist. to house. chem. and swim. pool

Release of dang.subs.: Cadmium (GL)

Release of dang.subs.: Lead (GL)

Surface hardness according to Mohs

The reference life (RSL)

Assessment of nat.radionuclide content

Norm

ISO 10545-2

ISO 10545-2

ISO 10545-2

ISO 10545-3

ISO 10545-8

ISO 10545-9

ISO 10545-11

ISO 10545-12

EN 14411

EN 12004:2007+A1:2012

EN 12004:2007+A1:2012

EN 12004:2007+A1:2012

EN 12004:2007+A1:2012

ISO 10545-10

NO TESTING 96/603 EHS

ISO 10545-13

ISO 10545-13

ISO 10545-15

ISO 10545-15

EN 101

ISO 14 025/EN 15804

CZ Imp.422/2016

STO 030-060753

± 0.5%

± 10%

Min. 95%

E>10%

Declared value

Required

Required

Declared value

Pass

Declared value

Declared value

Declared value

Declared value

Declared value

Class A1

Declared value

Min. B

Declared value

Declared value

Declared value

50 years

Max. index 1,0

LB/RAKO

± 0.5%

± 10%

Min. 95%

E>10%

Max. 0,000008 / K

Resistant

Resistant

Unsatisfactory

Pass

>=0,5 N/mm²

NPD*

NPD*

NPD*

0,6 mm/m

Class A1

B

B

NPD*

NPD*

Min. 7

50 years

Max. index 1,0

* No Performance Determined – NPD